

ROTAX® ENGINE	600R E-TEC	850 E-TEC				
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, 3-D R.A.V.E.™				
Cylinders	2					
Displacement	599.4 cc	849 cc				
Bore	72.3 mm	82 mm				
Stroke	73 mm	80.4 mm				
Maximum engine speed	8100 RPM	7900 RPM				
Carburation	Electronic Direct Injection	Electronic Direct Injection with additional booster injectors				
Recommended fuel type	Unleaded					
Minimum octane	95					
Fuel tank	37 liters					
Oil tank capacity (2-stroke)	3.4 liters					

Silver/Black		
3385 mm		
1120 mm		
1320 mm		
921 mm		
406 mm		
3923 mm		
64 mm PowderMax		

Orange/Full Moon

POWERTRAIN

Drive clutch type	pDrive with clickers			
Driven clutch type	QRS			
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder			
DRY WEIGHT				
Dry weight	240 kg	249 kg		

S	U	S	Ρ	Е	Ν	S	I	0	N	

LFS with bended lower A-Arms
KYB 36
PPS ² -DS+
KYB 36
KYB 36

FEATURES

Frame	Radien ²	Heated grips	Standard		
Skis	Blade DS+	Gauge	7.2-in. wide digital display		
Seating	Sport, 1-up	Windshield	Medium with side deflectors		
Handlebar	U-type steel with hooks,	Hitch	Standard		
	low grab handle	Visor Plug front / rear	Front		
Riser block height	145 mm	USB power outlet	Yes, in front compartment		
Starter	Electric and manual	Air radiator with fan	Yes		
Reverse	RER	LinQ attachment	Multi-LinQ plate		
Heated throttle lever	Standard				

* Vehicle overall length without snowflap.

©2023 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™,* and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

