

| ROTAX® ENGINE | 600 EFI |
|------------------------------|---------------------------|
| Engine details | Liquid-cooled, two-stroke |
| Cylinders | 2 |
| Displacement | 599.4 cc |
| Bore | 72.3 mm |
| Stroke | 73 mm |
| Maximum engine speed | 7500 RPM |
| Carburation | EFI |
| Recommended fuel type | Unleaded |
| Minimum octane | 95 |
| Fuel tank | 42 liters |
| Oil tank capacity (2-stroke) | 3.4 liters |

| COLOUR | Viper Red / Black |
|-------------------------|-------------------|
| DIMENSIONS | |
| Vehicle overall length* | 3240 mm |
| Vehicle overall width | 1200 mm |
| Vehicle overall height | 1500 mm |
| Ski stance | 996 mm |
| Track nominal width | 500 mm |
| Track nominal length | 3923 mm |
| Track profile height | 38 mm |

POWERTRAIN

| Drive clutch type | pDrive |
|--------------------|---|
| Driven clutch type | QRS |
| Brake system | Hydraulic brake with braided steel brake line, plastic master cylinder |

DRY WEIGHT

SUSPENSION

| Front suspension | LFS+ |
|------------------|----------------|
| Front shock | Motion Control |
| Rear suspension | EasyRide |
| Center shock | KYB 36 |
| Rear shock | KYB 36 |

FEATURES

| Frame | Radien-X |
|--------------------|-------------------------|
| Skis | Blade DS+ |
| Seating | Modular, 1-up |
| Handlebar | U-type steel with hooks |
| Riser block height | 145 mm |
| Starter | Electric and manual |
| | |

| RER |
|---------------------------------|
| Standard |
| Standard |
| Compact digital display |
| Extra high with side deflectors |
| Yes |
| Multi-LinQ plate |
| |



^{*} Vehicle overall length without snowflap.