



ROTAX® ENGINE	600R E-TEC
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™
Cylinders	2
Displacement	599.4 cc
Bore	72.3 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

COLOUR	Evo Red / Black		
DIMENSIONS			
Vehicle overall length*	3190 mm		
Vehicle overall width	1120 mm		
Vehicle overall height	1280 mm		
Ski stance	921 mm		
Track nominal width	381 mm		
Track nominal length	3923 mm		
Track profile height	64 mm PowderMax		

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

5	U	S	P	Е	N	S	Ю	N	

Front suspension	LFS		
Front shock	KYB 36		
Rear suspension	PPS ² -DS+		
Center shock	KYB 36		
Rear shock	KYB 36		

DRY WEIGHT

Dry weight 198 kg

FEATURES

Frame	Radien²
Skis	Blade DS+
Seating	Shredder DS, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	145 mm
Starter	Manual Electric (spring only)

RER		
Standard		
Standard		
4.5-in. digital display		
Yes, in front compartment		
2 pairs		



^{*} Vehicle overall length without snowflap.