



On & Off Trail + Mountain / Deep Snow + Family Fun

ROTAX® ENGINE	600R E-TEC
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™
Cylinders	2
Displacement	599.4 cc
Bore	72.3 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

Evo Red / Black
3160 mm
1200 mm
1280 mm
996 mm
406 mm
3705 mm
51 mm PowderMax

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

DRY WEIGHT

Dry weight	220 kg
------------	--------

SUSPENSION

Front suspension	LFS+
Front shock	KYB 36
Rear suspension	PPS ² -DS+
Center shock	KYB 36
Rear shock	KYB 36

FEATURES

Frame	Radien²
Skis	Blade DS+
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	145 mm
Starter	Electric and manual
Reverse	RER

Standard
Standard
4.5-in. digital display
Low
Front
Yes, in front compartment
2 pairs



^{*} Vehicle overall length without snowflap.