

ROTAX® ENGINE	850 E-TEC	
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	
Cylinders	2	
Displacement	849 cc	
Bore	82 mm	
Stroke	80.4 mm	
Maximum engine speed	7900 RPM	
Carburation	Electronic Direct Injection with additional booster injectors	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	42 liters	
Oil tank capacity (2-stroke)	3.4 liters	

Platinum Sliver Satin /
Evo Red
Black (spring only)

### DIMENSIONS

COLOUR

Vehicle overall length*	3230 mm	
Vehicle overall width	1200 mm	
Vehicle overall height	1230 mm	
Ski stance	996 mm	
Track nominal width	500 mm	
Track nominal length	3923 mm	
Track profile height	60 mm PowderMax	

#### POWERTRAIN

0.50	
QRS	
Hydraulic brake with braided steel brake line, plastic master cylinder	

#### **DRY WEIGHT**

Dry weight

# SUSPENSION

Front suspension	LFS+	
Front shock	KYB PRO 36 EA-3 R Kashima	
Rear suspension	EasyRide +	
Center shock	KYB 46 Plus Kashima	
Rear shock	KYB 46 Plus Kashima	

## FEATURES

Frame	Radien-X	Heated grips	Standard
Skis	Blade DS+		7.2-in. wide digital display /
Seating	Brutal, 1-up	Gauge	7.8-in panorama display (spring only)
Handlebar	U-type aluminium with hooks, low grab handle	Windshield	Low
Riser block height	120 mm	Visor Plug front / rear	Front
Starter	Electric and manual	USB power outlet	Yes, in front compartment
Reverse	RER	Air radiator with fan	Yes
Heated throttle lever	Standard	LinQ attachment	Multi-LinQ plate

259 kg

\* Vehicle overall length without snowflap.

©2023 Bombardier Recreational Products Inc., (BRP). All rights reserved. <sup>™</sup>,<sup>\*</sup> and the BRP logo are trademarks of BRP or its affiliates. <sup>†</sup>All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

