# MY24 OUTLANDER MAX 6X6 XU+ 1000 T



#### ENGINE 1000 60 kW (80 hp), Rotax® 976 cc V-twin, Туре liquid cooled Intelligent Throttle Control (iTC<sup>™</sup>) with Fuel Delivery System Electronic Fuel Injection (EFI) CVT Transmission Extra low L / H / N / R / P Selectable 4WD / 6WD / Lock 4WD with Visco-Drive Train 4Lok front differential **Driving Assistance** Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter **Power Steering** Tri-Mode Dynamic Power Steering (DPS) Speed Category Up to 60 km/h

#### HIGHLIGHTS

- Selectable 4WD / 6WD with Visco-4Lok† auto-locking front differential
- Tri-Mode Dynamic Power Steering (DPS)
- Continuously Variable Transmission (CVT) with extra low L-gear • 14 in. (35.6 cm) aluminum wheels
- 26 in. (66 cm) ITP Terracross tires
- 3,500-lb (1,588 kg) winch
- · Dump dual-level cargo box with modular accessories · Heated grips and throttle
- RF Digitally Encoded Security System (D.E.S.S.™)
- Speed limiter
- · Painted plastics for premium look

#### **DIMENSIONS / CAPACITIES**

FEATURES Gauge

Estimated Dry Weight *	597 kg
LxWxH	317 x 123 x 163.4 cm
Wheelbase	228.5 cm
Ground Clearance	27.9 cm
Seat Height	87.7 cm
Rack Capacity	Front: 45 kg / Rear: 318 kg
Storage Capacity	Dual-level cargo box with sidewalls and tailgate Rear: 18.5 gal (70 L)
Towing Capacity	907 kg trailer with brakes 674 kg trailer without brakes
Fuel Capacity	5.4 gal (20.5 L)

4.5 in. digital display

#### SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	Twin tube
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25.1 cm) travel
Rear Shocks	Twin tube
TIRES / WHEELS	
Front & Rear Tires	ITP† Terracross 26 x 8/10 x 14 in.

		5
	Instrumentation	DC Outlet, 15-A connector
ent -	Ingnition	RF Digitally Encoded Security System (D.E.S.S.™)
	Lighting	LED headlights
	Winch	3,500-lb (1,588 kg) winch
	T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn
	Seat	Reinforced seat skin Convertible Rack System (CRS)
	Handlebar	Standard with heated grips & throttle
	Protection	Heavy-Duty front bumper

## BRAKES

Wheels

Front	Dual 214 mm disc brakes with hydraulic
	twin-piston calipers
Rear	Dual 214 mm disc brakes with hydraulic twin-piston calipers

(66 x 20.3 / 25.4 x 35.6 cm)

14 in. (35.6 cm) cast-aluminum

### WARRANTY Factory warranty

2-year BRP limited warranty



**REQUEST A QUOTE** 



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, \* and the BRP logo are trademarks of BRP or its affiliates. \*Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.

