



Mountain / Deep Snow + Steep and deep + On & Off Trail + Utility

Orange/Full Moon

600R E-TEC	850 E-TEC
Liquid-cooled, two	-stroke, 3-D R.A.V.E.™
	2
599.4 cc	849 cc
72.3 mm	82 mm
73 mm	80.4 mm
8100 RPM	7900 RPM
Electronic Direct Injection	Electronic Direct Injection with additional booster injectors
Unl	eaded
	95
37	liters

3.4 liters

COLOUR	Silver/Black	
DIMENSIONS		
Vehicle overall length*	3385 mm	
Vehicle overall width	1120 mm	
Vehicle overall height	1320 mm	
Ski stance	921 mm	
Track nominal width	406 mm	
Track nominal length	3923 mm	
Track profile height	64 mm PowderMax	

POWERTRAIN

ROTAX® ENGINE

Maximum engine speed

Recommended fuel type Minimum octane Fuel tank

Oil tank capacity (2-stroke)

Engine details Cylinders Displacement

Carburation

Bore Stroke

Drive clutch type	pDrive with clickers	
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder	

SU	JSP	EN	ISI	ON

LFS with curved lower A-Arms
KYB 36
PPS ² -DS+
KYB 36
KYB 36

DRY WEIGHT

Dry weight	240 kg	249 kg
------------	--------	--------

FEATURES

Frame	Radien²	
Skis	Blade DS+	
Seating	Sport, 1-up heated	
Handlebar	U-type steel with hooks, low grab handle	
Riser block height	145 mm	
Starter	Electric and manual	
Reverse	RER	
Heated throttle lever	Standard	

Standard	
7.2" wide digital display	
Medium with side deflectors	
Standard	
Front	
Yes, in front compartment	
Yes	
Multi-LinQ plate	



^{*} Vehicle overall length without snowflap.