

| ROTAX® ENGINE | 600 ACE | 600 EFI |
|------------------------------|---|------------------------------|
| Engine details | Liquid-cooled, four- stroke D.O.H.C. | Liquid-cooled, two-stroke |
| Cylinders | 2 | |
| Displacement | 600 cc | 599.4 cc |
| Bore | 74 mm | 72.3 mm |
| Stroke | 69.7 mm | 73 mm |
| Maximum engine speed | 7250 RPM | 7500 RPM |
| Carburation | EFI | |
| Recommended fuel type | Unleaded | |
| Minimum octane | 95 | |
| Fuel tank | 42 liters | |
| Oil tank capacity (2-stroke) | 3.4 liters | |

| COLOUR | Viper Red / Black |
|-------------------------|-------------------|
| DIMENSIONS | |
| Vehicle overall length* | 3240 mm |
| Vehicle overall width | 1200 mm |
| Vehicle overall height | 1500 mm |
| Ski stance | 996 mm |
| Track nominal width | 500 mm |
| Track nominal length | 3923 mm |
| Track profile height | 38 mm |

POWERTRAIN

| Drive clutch type | eDrive II | pDrive |
|--------------------|---|--------|
| Driven clutch type | QRS | |
| Brake system | Hydraulic brake with braided steel brake line, aluminium master cylinder | |

SUSPENSION

| Front suspension | LFS+ |
|------------------|-----------|
| Front shock | KYB 36 |
| Rear suspension | EasyRide+ |
| Center shock | KYB 36 |
| Rear shock | KYB 36 |

DRY WEIGHT

|--|

FEATURES

| Frame | Radien-X | |
|--------------------|---|--|
| Skis | Blade DS+ | |
| Seating | Modular, 1-up | |
| Handlebar | U-type steel with hooks | |
| Riser block height | 145 mm | |
| Starter | Electric and manual (EFI) Electric (ACE) | |
| Reverse | RER (EFI) Electromechanical (ACE) | |

| Heated throttle lever | Standard | |
|-------------------------|---------------------------------|--|
| Heated grips | Standard | |
| Gauge | 4.5" digital display | |
| Windshield | Extra high with side deflectors | |
| Visor Plug front / rear | Front | |
| USB power outlet | Yes, in front compartment | |
| Air radiator with fan | Yes | |
| LinQ attachment | Multi-LinQ plate | |



^{*} Vehicle overall length without snowflap.