

ROTAX® ENGINE	900 ACE	900 ACE Turbo
Engine details	Liquid-cooled, four- stroke D.O.H.C.	Liquid-cooled, four- stroke D.O.H.C., turbo- charged
Cylinders	-	3
Displacement	899.0 cc	
Bore	74 mm	
Stroke	69.7 mm	
Maximum engine speed	7250 RPM 7750 RPM	
Carburation	EFI	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	42 liters	

co	0	ID	
$\mathbf{c}\mathbf{c}$	LV	UR	

**SUSPENSION** 

**Front suspension** 

**Rear suspension** 

Front shock

**Center shock** 

**Rear shock** 

309 kg

## Orange/ Full Moon Silver/Black

LFS+

with curved lower A-Arms KYB 36

Articulated EasyRide+

with adjustment

KYB 36

KYB 36

DIMENSIONS	
Vehicle overall length*	3250 mm
Vehicle overall width	1200 mm
Vehicle overall height	1450 mm
Ski stance	996 mm
Track nominal width	600 mm
Track nominal length	3923 mm
Track profile height	38 mm

## POWERTRAIN

2F/N/R with push-button reverse	
pDrive with slider shoes	
QRS	
Hydraulic brake with braided steel brake line, aluminium master cylinder	

304 kg

## **DRY WEIGHT**

Drv	weight
	weight

## FEATURES

Frame	Radien-X
Skis	Blade DS+
Seating	Modular, 1-up heated
Handlebar	U-type steel with hooks, low grab handle
Riser block height	145 mm
Starter	Electric
Reverse	Electromechanical
Heated throttle lever	Standard
Heated grips	Standard

Gauge	7.2" wide digital display
Windshield	Extra high with side deflectors
Hitch	Standard
Visor Plug front / rear	Front
USB power outlet	Yes, in front compartment
Air radiator with fan	Yes
LinQ attachment	Multi-LinQ plate

\* Vehicle overall length without snowflap.

©2024 Bombardier Recreational Products Inc., (BRP). All rights reserved. <sup>™</sup>,\* and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

