



ROTAX® ENGINE	900 ACE	900 ACE Turbo
Engine details	Liquid-cooled, four- stroke D.O.H.C.	Liquid-cooled, four- stroke D.O.H.C., turbocharged
Cylinders	3	3
Displacement	899.0 cc	
Bore	74 mm	
Stroke	69.7 mm	
Maximum engine speed	7250 RPM	7750 RPM
Carburation	Е	FI
Recommended fuel type	Unle	aded
Minimum octane	95	
Fuel tank	37 liters	

3180 mm
1280 mm
1320 mm
1097 mm
381 mm
3705 mm
41 mm Cobra

POWERTRAIN

pDrive
QRS
Hydraulic brake with braided steel brake line, aluminium master cylinder

S	U	S	P	Е	N	S	Ю	N	

Front suspension	LFS+		
Front shock	KYB 36 Plus R		
Rear suspension	PPS ³		
Center shock	KYB 36 Plus Kashima		
Rear shock	KYB 46 Plus Kashima		

DRY WEIGHT

Dry weight 247 kg (1 up) 258 kg (2 up)	252 kg (1 up) 263 kg (2 up)
--	--------------------------------

FEATURES

Frame	Radien²	
Skis	Blade DS+	
Seating	Sport, 1-up or 2-up heated	
Handlebar	U-type steel with hooks	
Riser block height	120 mm	
Starter	Electric	
Reverse	Electromechanical	
Heated throttle lever	Standard	

Heated grips	Standard	
Gauge	7.2" wide digital display / 10.25" Touchscreen Display (spring only on Turbo)	
Windshield	Medium with side deflectors	
Visor Plug front / rear	Front and rear (2-up)	
USB power outlet	Yes, in front compartment	
LinQ attachment	2 pairs	



^{*} Vehicle overall length without snowflap.