



ROTAX® ENGINE	900 ACE	900 ACE Turbo
Engine details	Liquid-cooled, four- stroke D.O.H.C.	Liquid-cooled, four-stroke D.O.H.C., turbocharged
Cylinders	3	
Displacement	899.0 cc	
Bore	74 mm	
Stroke	69.7 mm	
Maximum engine speed	7250 RPM	7750 RPM
Carburation	EFI	
Recommended fuel type	Unleaded	
Minimum octane	95	
Fuel tank	42 liters	

COLOUR Noble Bronze / B	
DIMENSIONS	
Vehicle overall length*	3240 mm
Vehicle overall width	1200 mm 1280 mm (w. 2up seat)
Vehicle overall height	1500 mm
Ski stance	996 mm 1097 mm (w. 2up seat)
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	44 mm PowderMax / 38 mm Ice Cobra Silent (spring only)

SUSPENSION

Gearbox	2F/N/R with push-button reverse	
Drive clutch type	pDrive with slider shoes	pDrive
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line aluminium master cylinder	

287 kg (1 up)

298 kg (2 up)

298 kg (1 up)

309 kg (2 up)

Front suspension	LFS+ with curved lower A-Arms (1-up) LFS+ (2-up)
Front shock	KYB 36 Plus (1-up) KYB 36 Plus R (2-up)
Rear suspension	Articulated EasyRide+ with adjustment
Center shock	KYB 46 Plus Kashima
Rear shock	KYB 46 Plus Kashima

FEATURES

Dry weight

Frame	Radien-X	
Skis	Blade DS+	
Seating	Modular, 1-up or 2-up heated	
Handlebar	U-type steel with hooks, low grab handle	
Riser block height	145 mm	
Starter	Electric	
Reverse	Electromechanical	

Heated throttle lever	Standard	
Heated grips	Standard	
Gauge	7.2" wide digital display	
Windshield	Extra high with side deflectors	
Hitch	Standard	
Visor Plug front / rear	Front and rear (2-up)	
USB power outlet	Front	
Air radiator with fan	Yes	
LinQ attachment	Multi-LinQ plate	



^{*} Vehicle overall length without snowflap.