

ROTAX® ENGINE	600R E-TEC	COLOUR
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	
Cylinders	2	DIMENSIO
Displacement	599.4 cc	Vehicle ove
Bore	72.3 mm	venicie ove
Stroke	73 mm	Vehicle ove
Maximum engine speed	8100 RPM	Vehicle ove
Carburation	Electronic Direct Injection	Ski stance
Recommended fuel type	Unleaded	Track nomi
Minimum octane	95	Track nomi
Fuel tank	37 liters	
Oil tank capacity (2-stroke)	3.4 liters	Track profil

<b>—</b>
Viper Red / Black

# DIMENSIONS

Vehicle overall length*	3060 mm (3700) 3190 mm (3900)	
Vehicle overall width	1120 mm	
Vehicle overall height	1280 mm	
Ski stance	921 mm	
Track nominal width	381 mm	
Track nominal length	3705 mm 3923 mm	
Track profile height	64 mm PowderMax	

### POWERTRAIN

Drive clutch type	pDrive with clickers	
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, aluminium master cylinder	

#### **DRY WEIGHT**

Dry weight	3700: 194 kg
Dry weight	3900: 198 kg

### SUSPENSION

Front suspension	LFS
Front shock	KYB 36
Rear suspension	PPS <sup>2</sup> -DS+
Center shock	KYB 36
Rear shock	KYB 36

## **FEATURES**

Radien <sup>2</sup>
Blade DS+
Mountain Light, 1-up
U-type aluminium with hooks, low grab handle
120 mm
Manual Electric (spring only)

verse RER	
Standard	
Standard	
4.5" digital display	
Yes, in front compartment	
2 pairs	

\* Vehicle overall length without snowflap.

