2025 TUNDRA[™] LE



// PACKAGE HIGHLIGHTS

- Rotax® 600 EFI and 600 ACE™ engine with 650 W magneto available
- KYB† 36 rear shock
- Painted tunnel
- 4.5 in. digital display
- LTS telescopic front suspension
- SC†-5U articulating rear suspension with locking mechanism (no tool required)
- Brembo† brake
- Heavy-duty rear bumper with tongue-type hitch
- Air radiator with fan
- Standard electric start

- Deep snow running boards with large openings
- Standard with two sets of LinQ® attachment points
- Pilot™ DS 2 skis
- Low handlebar strap

ROTAX ENGINE	600 EFI	600 ACE
Engine details	Liquid-cooled, two-stroke	Liquid-cooled, four-stroke D.O.H.C., dry sump
Horsepower**	85	62
Cylinders - Displacement	2 - 599.4 cc	2 - 600 cc
Bore - Stroke (mm)	72.3 – 73	73 - 69.7
Fuel system	EFI	EFI
Fuel type – Octane	Regular unleaded – 87	Regular unleaded – 87
Fuel tank (L/US gal)	36/9.5	36/9.5
Oil tank capacity (L/qt)	3.4/3.6	2.1/2.2
POWERTRAIN		
Drive clutch	pDrive™	eDrive™ 2
Driven clutch	QRS	QRS
Drive sprocket pitch (mm/in.)	73/2.86	
DRY WEIGHT		
Dry weight (lb)	483	507
DIMENSIONS		
Vehicle overall length (mm/in.)	3,259/129.3	
Vehicle overall width (mm/in.)	994/39.1	
Vehicle overall height (mm/in.)	1,513/59.6	
Ski stance (mm/in.)	813/32	
Available tracks (in.)	Charger:	
(Length x width x profile)	154 x 16 x 1.5	

Black		
SUSPENSION		
Front suspension	LTS	
Front shock	Motion Control	
Front suspension travel (mm/in.)	150/5.9	
Rear suspension	SC-5U	
Center shock	Motion Control	
Rear shock	KYB 36	
Rear suspension travel (mm/in.)	239/9.4	
FEATURES		
Platform	REV® Gen4	
Headlights	Halogen	
Skis	Pilot DS 2	
Seating	Trail narrow compact	
Handlebar	Standard with J-hooks/ Grab handle	
Riser block height (mm/in.)	145/5.7	
Starter	Electric	
Reverse	RER™ (600 EFI) Mechanical (600 ACE)	
Air radiator	Fan	
Brake system	Brembo	
Heated throttle lever/grips	Standard	
Gauge type	4.5 in. digital	
Windshield	Medium	
Runner (in.) – Carbide (in.)	3/8 square - 4	
Bumpers (front/rear)	Std/Heavy-duty	

2025 TUNDRA LE

// FEATURE HIGHLIGHTS



1 Rotax 600 ACE and 600 EFI engines

Two easy-to-own, reliable and fuel-efficient choices. 62 hp* [600 ACE] or 85 hp* [600 EFI] versions ensure great performance and incredible value.

(See website for image)

2 154 in. track length

Provides extra flotation and traction when riding in deep snow.



3 LTS front suspension

Industry-exclusive telescopic front suspension enables a large, flat belly pan for exceptional deep snow flotation.



5

TUNDRA LE 600 EFI SHOWN



4 Air radiator with fan

Extra cooling capacity when pulling a heavy load, in low-snow conditions or at low speed.



5 SC-5U articulating rear suspension

The articulated rail maximizes deep snow traction in reverse, and its toolless locking mechanism is ideal for towing.



6 Heavy-duty rear bumper

For extra protection and extreme utility.



